


- アルミニウム，銅合金専用のエンドミルです。
- アルミのドライ加工ができます。

This is suitable for Dry-milling of Aluminum with DLC coat.



LIST 9330

オーダ方法

2DLCM 外径

単位 (Unit) : mm / 円 (¥)

外径 Dc	溝刃長 ℓ	全長 L	シャンク径 Ds	在庫 Stock	参考価格 Price
1	3	40	4	●	4,140
1.1				-	
1.2				-	
1.3				-	
1.4				-	
1.5	4			●	4,140
1.6				-	
1.7				-	
1.8				-	
1.9	5			□	-
2		-			
2.1	6	●	4,090		
2.2		-			
2.3	-				
2.4	8	□	-		
2.5		●	4,090		
2.6		-			
2.7		-			
2.8		-			
2.9		-			
3		-			
3.1		10	●	4,090	
3.2	-				
3.3	-				
3.4	-				
3.5	●		5,140		
3.6	-				
3.7	-				
3.8	-				
3.9	-				
4	11		●	5,140	
4.1		-			
4.2		-			
4.3		-			
4.4		-			
4.5		●	5,540		
4.6		-			
4.7		-			
4.8		-			
4.9		-			
5	13	●	5,540		
5.1		-			
5.2		-			
5.3		-			
5.4		-			
5.5		-			
5.6		●	6,270		
5.7		-			
5.8		-			
5.9		-			
6	16	●	5,750		
6.1		-			
6.2		-			
6.3		-			
6.4		-			
6.5		-			
6.6		-			
6.7		-			
6.8		-			
6.9		-			
7	8	●	6,860		
7.1		-			
7.2		-			
7.3		-			

外径 Dc	溝刃長 ℓ	全長 L	シャンク径 Ds	在庫 Stock	参考価格 Price
7.4	16	60	8	-	-
7.5				-	
7.6				-	
7.7				-	
7.8				-	
7.9				-	
8				-	
8.1				-	
8.2				-	
8.3				-	
8.4	19	70	10	□	-
8.5				-	
8.6				-	
8.7				-	
8.8				-	
8.9				-	
9				-	
9.1				-	
9.2				-	
9.3				-	
9.4	-				
9.5	-				
9.6	-				
9.7	-				
9.8	-				
9.9	-				
10	22	75	12	●	9,260
10.1				-	
10.2				-	
10.3				-	
10.4				-	
10.5				-	
10.6				-	
10.7				-	
10.8				-	
10.9				-	
11	-				
11.1	-				
11.2	-				
11.3	-				
11.4	-				
11.5	-				
11.6	-				
11.7	-				
11.8	-				
11.9	-				
12	26	90	16	●	12,200
16				-	
20				-	
32				-	
38				-	
20	100	120	20	●	23,700
24				-	
28				-	
32				-	
36				-	

□は特定代理店在庫品です。
 Available for Japan customers only.

外径 (mm) Dc		許容差 (mm) Tolerance
を超え Above	以下 Up to	
	3	-0.014 ~ -0.028
	6	-0.020 ~ -0.038
	10	-0.025 ~ -0.047
	16	-0.032 ~ -0.059

商品紹介	
DLC ミルアルミ用	F-20
DLCハイスミル	B-116

DLC コーティングが施してあります。DLC コーティングは潤滑性が高く耐凝着性に優れています。