


# AQDED3F

アクアドリル底刃付き 3 フルート



NACHI



- 鑄抜き穴や穴ぐりの高精度加工に最適です。
- 位置矯正力に優れ、高能率加工を実現します。



TY コード	外径	溝長	全長	シャンク	区分
NA16020	3	16	48	3	○
NA16021	3.1	18	50	4	■
NA16022	3.2	18	50	4	■
NA16023	3.3	18	50	4	■
NA16024	3.4	20	52	4	■
NA16025	3.5	20	52	4	■
NA16026	3.6	20	52	4	■
NA16027	3.7	20	52	4	■
NA16028	3.8	22	54	4	■
NA16029	3.9	22	54	4	■
NA16030	4	22	54	4	○
NA16031	4.1	22	66	6	■
NA16032	4.2	22	66	6	■
NA16033	4.3	24	68	6	■
NA16034	4.4	24	68	6	■
NA16035	4.5	24	68	6	■
NA16036	4.6	24	68	6	■
NA16037	4.7	24	68	6	■
NA16038	4.8	26	70	6	■
NA16039	4.9	26	70	6	■
NA16040	5	26	70	6	○
NA16041	5.1	26	70	6	■
NA16042	5.2	26	70	6	■
NA16043	5.3	26	70	6	■
NA16044	5.4	28	72	6	■
NA16045	5.5	28	72	6	■
NA16046	5.6	28	72	6	■
NA16047	5.7	28	72	6	■
NA16048	5.8	28	72	6	■
NA16049	5.9	28	72	6	■
NA16050	6	28	72	6	○
NA16051	6.1	31	75	8	■
NA16052	6.2	31	75	8	■
NA16053	6.3	31	75	8	■
NA16054	6.4	31	75	8	■
NA16055	6.5	31	75	8	■
NA16056	6.6	31	75	8	■
NA16057	6.7	31	75	8	■
NA16058	6.8	34	78	8	■
NA16059	6.9	34	78	8	■
NA16060	7	34	78	8	○
NA16061	7.1	34	78	8	■
NA16062	7.2	34	78	8	■
NA16063	7.3	34	78	8	■
NA16064	7.4	34	78	8	■
NA16065	7.5	34	78	8	■

TY コード	外径	溝長	全長	シャンク	区分
NA16066	7.6	37	81	8	■
NA16067	7.7	37	81	8	■
NA16068	7.8	37	81	8	■
NA16069	7.9	37	81	8	■
NA16070	8	37	81	8	○
NA16071	8.1	37	87	10	■
NA16072	8.2	37	87	10	■
NA16073	8.3	37	87	10	■
NA16074	8.4	37	87	10	■
NA16075	8.5	37	87	10	■
NA16076	8.6	40	90	10	■
NA16077	8.7	40	90	10	■
NA16078	8.8	40	90	10	■
NA16079	8.9	40	90	10	■
NA16080	9	40	90	10	○
NA16081	9.1	40	90	10	■
NA16082	9.2	40	90	10	■
NA16083	9.3	40	90	10	■
NA16084	9.4	40	90	10	■
NA16085	9.5	40	90	10	■
NA16086	9.6	43	93	10	■
NA16087	9.7	43	93	10	■
NA16088	9.8	43	93	10	■
NA16089	9.9	43	93	10	■
NA16090	10	43	93	10	○
NA16091	10.1	43	100	12	■
NA16092	10.2	43	100	12	■
NA16093	10.3	43	100	12	■
NA16094	10.4	43	100	12	■
NA16095	10.5	43	100	12	■
NA16096	10.6	43	100	12	■
NA16097	10.7	47	104	12	■
NA16098	10.8	47	104	12	■
NA16099	10.9	47	104	12	■
NA16100	11	47	104	12	○
NA16101	11.1	47	104	12	■
NA16102	11.2	47	104	12	■
NA16103	11.3	47	104	12	■
NA16104	11.4	47	104	12	■
NA16105	11.5	47	104	12	■
NA16106	11.6	47	104	12	■
NA16107	11.7	47	104	12	■
NA16108	11.8	47	104	12	■
NA16109	11.9	51	108	12	■
NA16110	12	51	108	12	○

低炭素鋼 軟鋼	炭素鋼 合金鋼	プレハードン鋼 高合金鋼	調質鋼	焼入鋼 Hardened Steels		ステンレス鋼		耐熱合金	鋳鉄	アルミ合金	銅・銅合金
				SKD,SKH 30 ~ 40HRC	40 ~ 50HRC	50 ~ 65HRC	SUS304				
◎	○			×	×	×			◎		

◎標準品 ■オリジナル品