


- 生材から焼入材まで幅広く対応できます。
- 金型の型彫り加工に適しています。

This end mill is suited for used in profile milling.



LIST 9278

オーダ方法

2PLXSR ボール半径

単位 (Unit) : mm / 円 (¥)

ボール半径 R	外径 Dc	刃長 ℓ	全長 L	シャンク径 Ds	在庫 Stock
0.2	0.4	0.8	45	4	□
0.25	0.5	1			
0.3	0.6	1.2	50		
0.35	0.7				
0.4	0.8	1.6	55		
0.45	0.9				
0.5	1	2.5	60		
0.55	1.1				
0.6	1.2	3	70		
0.65	1.3				
0.7	1.4	3.5	80		
0.75	1.5				
0.8	1.6	4	90		
0.85	1.7				
0.9	1.8	4.5	100		
0.95	1.9				
1	2	5	110		
1.05	2.1				
1.1	2.2	6	120		
1.15	2.3				
1.2	2.4	7	130		
1.25	2.5				
1.3	2.6	8	140		
1.35	2.7				
1.4	2.8	9	150		
1.45	2.9				
1.5	3	10	160		
1.55	3.1				
1.6	3.2	11	170		
1.65	3.3				
1.7	3.4	12	180		
1.75	3.5				
1.8	3.6	13	190		
1.85	3.7				
1.9	3.8	14	200		
1.95	3.9				
2	4	15	210		
2.05	4.1				
2.1	4.2	16	220		
2.15	4.3				
2.2	4.4	17	230		
2.25	4.5				
2.3	4.6	18	240		
2.35	4.7				
2.4	4.8	19	250		
2.45	4.9				
2.5	5	20	260		
2.55	5.1				
2.6	5.2	21	270		
2.65	5.3				
2.7	5.4	22	280		
2.75	5.5				
2.8	5.6	23	290		
2.85	5.7				
2.9	5.8	24	300		
2.95	5.9				
3	6	25	310		
3.05	6.1				
3.1	6.2	26	320		
3.15	6.3				
3.2	6.4	27	330		
3.25	6.5				
3.3	6.6	28	340		
3.35	6.7				
3.4	6.8	29	350		
3.45	6.9				

ボール半径 R	外径 Dc	刃長 ℓ	全長 L	シャンク径 Ds	在庫 Stock
3.5	7	14	100	6	□
3.55	7.1				
3.6	7.2	16	110	8	□
3.65	7.3				
3.7	7.4	18	120	10	□
3.75	7.5				
3.8	7.6	20	130	12	□
3.85	7.7				
3.9	7.8	22	140	14	□
3.95	7.9				
4	8	24	150	16	□
4.05	8.1				
4.1	8.2	26	160	18	□
4.15	8.3				
4.2	8.4	28	170	20	□
4.25	8.5				
4.3	8.6	30	180	22	□
4.35	8.7				
4.4	8.8	32	190	24	□
4.45	8.9				
4.5	9	34	200	26	□
4.55	9.1				
4.6	9.2	36	210	28	□
4.65	9.3				
4.7	9.4	38	220	30	□
4.75	9.5				
4.8	9.6	40	230	32	□
4.85	9.7				
4.9	9.8	42	240	34	□
4.95	9.9				
5	10	44	250	36	□
5.25	10.5				
5.5	11	46	260	38	□
5.75	11.5				
6	12	48	270	40	□
6.25	12.5				
6.5	13	50	280	42	□
6.75	13.5				
7	14	52	290	44	□
7.25	14.5				
7.5	15	54	300	46	□
7.75	15.5				
8	16	56	310	48	□
8.25	16.5				
8.5	17	58	320	50	□
8.75	17.5				
9	18	60	330	52	□
9.25	18.5				
9.5	19	62	340	54	□
9.75	19.5				
10	20	64	350	56	□
10.5	21				
11	22	66	360	58	□
11.5	23				
12	24	68	370	60	□
12.5	25				
13	26	70	380	62	□
13.5	27				
14	28	72	390	64	□
14.5	29				
15	30	74	400	66	□

□は特定代理店在庫品です。

Available for Japan customers only.

ボール半径 (mm) R		許容差 (mm) Tolerance	
を超え Above	以下 Up to	外径 Dc	R
	3	-0.004 ~ -0.022	±0.01
3	5	-0.005 ~ -0.027	
5	9	-0.006 ~ -0.033	
9		-0.007 ~ -0.040	