



MRS-GDN


マイクロレボリューションドリル



フォーファセットポイント
Four Facet point
(Dc ≤ 1.18mm)



X形シンニング
X thinning
(Dc ≥ 1.19mm)



【オリジナル商品】

●材質：超超微粒子超硬合金 ●表面処理：スームコートコート ●外径許容差：0～-0.008mm

・ステンレス鋼などの小径加工に変革をもたらす



TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
OS31617	0.1	0.9	38	3	□
OS31618	0.11	0.9	38	3	□
OS31619	0.12	1.1	38	3	□
OS31620	0.13	1.1	38	3	□
OS31621	0.14	1.1	38	3	□
OS31622	0.15	1.4	38	3	□
OS31623	0.16	1.4	38	3	□
OS31624	0.17	1.4	38	3	□
OS31625	0.18	1.7	38	3	□
OS31626	0.19	1.7	38	3	□
OS31627	0.2	2	38	3	□
OS31628	0.21	2	38	3	□
OS31629	0.22	2	38	3	□
OS31630	0.23	2	38	3	□
OS31631	0.24	2	38	3	□
OS31632	0.25	2	38	3	□
OS31633	0.26	2	38	3	□
OS31634	0.27	2	38	3	□
OS31635	0.28	2	38	3	□
OS31636	0.29	2	38	3	□
OS31637	0.3	2	38	3	□
OS31638	0.31	3	38	3	□
OS31639	0.32	3	38	3	□
OS31640	0.33	3	38	3	□
OS31641	0.34	3	38	3	□
OS31642	0.35	3	38	3	□
OS31643	0.36	3	38	3	□
OS31644	0.37	3	38	3	□
OS31645	0.38	3	38	3	□
OS31646	0.39	4	38	3	□
OS31647	0.4	4	38	3	□
OS31648	0.41	4	38	3	□
OS31649	0.42	4	38	3	□
OS31650	0.43	4	38	3	□
OS31651	0.44	4	38	3	□
OS31652	0.45	4	38	3	□
OS31653	0.46	4	38	3	□
OS31654	0.47	4	38	3	□
OS31655	0.48	4	38	3	□
OS31656	0.49	4.5	38	3	□
OS31657	0.5	4.5	42	3	□
OS31658	0.51	4.5	42	3	□
OS31659	0.52	4.5	42	3	□
OS31660	0.53	4.5	42	3	□
OS31661	0.54	5.5	42	3	□
OS31662	0.55	5.5	42	3	□
OS31663	0.56	5.5	42	3	□
OS31664	0.57	5.5	42	3	□
OS31665	0.58	5.5	42	3	□
OS31666	0.59	5.5	42	3	□
OS31667	0.6	5.5	42	3	□
OS31668	0.61	6	42	3	□
OS31669	0.62	6	42	3	□
OS31670	0.63	6	42	3	□
OS31671	0.64	6	42	3	□
OS31672	0.65	6	42	3	□
OS31673	0.66	6	42	3	□

TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
OS31674	0.67	6	42	3	□
OS31675	0.68	7	42	3	□
OS31676	0.69	7	42	3	□
OS31677	0.7	7	42	3	□
OS31678	0.71	7	42	3	□
OS31679	0.72	7	42	3	□
OS31680	0.73	7	42	3	□
OS31681	0.74	7	42	3	□
OS31682	0.75	7	42	3	□
OS31683	0.76	7.5	42	3	□
OS31684	0.77	7.5	42	3	□
OS31685	0.78	7.5	42	3	□
OS31686	0.79	7.5	42	3	□
OS31687	0.8	7.5	42	3	□
OS31688	0.81	7.5	42	3	□
OS31689	0.82	7.5	42	3	□
OS31690	0.83	7.5	42	3	□
OS31691	0.84	7.5	42	3	□
OS31692	0.85	7.5	42	3	□
OS31693	0.86	8.5	42	3	□
OS31694	0.87	8.5	42	3	□
OS31695	0.88	8.5	42	3	□
OS31696	0.89	8.5	42	3	□
OS31697	0.9	8.5	42	3	□
OS31698	0.91	8.5	42	3	□
OS31699	0.92	8.5	42	3	□
OS31700	0.93	8.5	42	3	□
OS31701	0.94	8.5	42	3	□
OS31702	0.95	8.5	42	3	□
OS31703	0.96	9	42	3	□
OS31704	0.97	9	42	3	□
OS31705	0.98	9	42	3	□
OS31706	0.99	9	42	3	□
OS31707	1	9	42	3	□
OS31708	1.01	9	42	3	□
OS31709	1.02	9	42	3	□
OS31710	1.03	9	42	3	□
OS31711	1.04	9	42	3	□
OS31712	1.05	9	42	3	□
OS31713	1.06	9	42	3	□
OS31714	1.07	11	50	3	□
OS31715	1.08	11	50	3	□
OS31716	1.09	11	50	3	□
OS31717	1.1	11	50	3	□
OS31718	1.11	11	50	3	□
OS31719	1.12	11	50	3	□
OS31720	1.13	11	50	3	□
OS31721	1.14	11	50	3	□
OS31722	1.15	11	50	3	□
OS31723	1.16	11	50	3	□
OS31724	1.17	11	50	3	□
OS31725	1.18	11	50	3	□
OS31726	1.19	12	50	3	□
OS31727	1.2	12	50	3	□
OS31728	1.21	12	50	3	□
OS31729	1.22	12	50	3	□
OS31730	1.23	12	50	3	□

●標準品 □オリジナル品

MRS-GDN


マイクロレボリューションドリル



フォーファセットポイント
Four Facet point
(Dc ≦ 1.18mm)



X シンニング
X thinning
(Dc ≧ 1.19mm)



【オリジナル商品】

●材質：超超微粒子超硬合金 ●表面処理：スムースコートコート ●外径許容差：0 ~ - 0.008mm

・ステンレス鋼などの小径加工に変革をもたらす



TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
OS31731	1.24	12	50	3	□
OS31732	1.25	12	50	3	□
OS31733	1.26	12	50	3	□
OS31734	1.27	12	50	3	□
OS31735	1.28	12	50	3	□
OS31736	1.29	12	50	3	□
OS31737	1.3	12	50	3	□
OS31738	1.31	12	50	3	□
OS31739	1.32	12	50	3	□
OS31740	1.33	14	50	3	□
OS31741	1.34	14	50	3	□
OS31742	1.35	14	50	3	□
OS31743	1.36	14	50	3	□
OS31744	1.37	14	50	3	□
OS31745	1.38	14	50	3	□
OS31746	1.39	14	50	3	□
OS31747	1.4	14	50	3	□
OS31748	1.41	14	50	3	□
OS31749	1.42	14	50	3	□
OS31750	1.43	14	50	3	□
OS31751	1.44	14	50	3	□
OS31752	1.45	14	50	3	□
OS31753	1.46	14	50	3	□
OS31754	1.47	14	50	3	□
OS31755	1.48	14	50	3	□
OS31756	1.49	14	50	3	□
OS31757	1.5	14	50	3	□
OS31758	1.51	15	50	3	□
OS31759	1.52	15	50	3	□
OS31760	1.53	15	50	3	□
OS31761	1.54	15	50	3	□
OS31762	1.55	15	50	3	□
OS31763	1.56	15	50	3	□
OS31764	1.57	15	50	3	□
OS31765	1.58	15	50	3	□
OS31766	1.59	15	50	3	□
OS31767	1.6	15	50	3	□
OS31768	1.61	15	54	3	□
OS31769	1.62	15	54	3	□
OS31770	1.63	15	54	3	□
OS31771	1.64	15	54	3	□
OS31772	1.65	15	54	3	□
OS31773	1.66	15	54	3	□
OS31774	1.67	15	54	3	□
OS31775	1.68	15	54	3	□
OS31776	1.69	15	54	3	□
OS31777	1.7	15	54	3	□
OS31778	1.71	17	54	3	□
OS31779	1.72	17	54	3	□
OS31780	1.73	17	54	3	□
OS31781	1.74	17	54	3	□
OS31782	1.75	17	54	3	□
OS31783	1.76	17	54	3	□
OS31784	1.77	17	54	3	□
OS31785	1.78	17	54	3	□
OS31786	1.79	17	54	3	□
OS31787	1.8	17	54	3	□

TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
OS31788	1.81	17	54	3	□
OS31789	1.82	17	54	3	□
OS31790	1.83	17	54	3	□
OS31791	1.84	17	54	3	□
OS31792	1.85	17	54	3	□
OS31793	1.86	17	54	3	□
OS31794	1.87	17	54	3	□
OS31795	1.88	17	54	3	□
OS31796	1.89	17	54	3	□
OS31797	1.9	17	54	3	□
OS31798	1.91	18	54	3	□
OS31799	1.92	18	54	3	□
OS31800	1.93	18	54	3	□
OS31801	1.94	18	54	3	□
OS31802	1.95	18	54	3	□
OS31803	1.96	18	54	3	□
OS31804	1.97	18	54	3	□
OS31805	1.98	18	54	3	□
OS31806	1.99	18	54	3	□
OS31807	2	18	54	3	□
OS31808	2.01	18	58	3	□
OS31809	2.02	18	58	3	□
OS31810	2.03	18	58	3	□
OS31811	2.04	18	58	3	□
OS31812	2.05	18	58	3	□
OS31813	2.06	18	58	3	□
OS31814	2.07	18	58	3	□
OS31815	2.08	18	58	3	□
OS31816	2.09	18	58	3	□
OS31817	2.1	18	58	3	□
OS31818	2.11	18	58	3	□
OS31819	2.12	18	58	3	□
OS31820	2.13	20	58	3	□
OS31821	2.14	20	58	3	□
OS31822	2.15	20	58	3	□
OS31823	2.16	20	58	3	□
OS31824	2.17	20	58	3	□
OS31825	2.18	20	58	3	□
OS31826	2.19	20	58	3	□
OS31827	2.2	20	58	3	□
OS31828	2.21	20	58	3	□
OS31829	2.22	20	58	3	□
OS31830	2.23	20	58	3	□
OS31831	2.24	20	58	3	□
OS31832	2.25	20	58	3	□
OS31833	2.26	20	58	3	□
OS31834	2.27	20	58	3	□
OS31835	2.28	20	58	3	□
OS31836	2.29	20	58	3	□
OS31837	2.3	20	58	3	□
OS31838	2.31	20	58	3	□
OS31839	2.32	20	58	3	□
OS31840	2.33	20	58	3	□
OS31841	2.34	20	58	3	□
OS31842	2.35	20	58	3	□
OS31843	2.36	20	58	3	□
OS31844	2.37	22	58	3	□

●標準品 □オリジナル品



MRS-GDN


マイクロレボリューションドリル



フォーファセットポイント
Four Facet point
(Dc ≤ 1.18mm)



X形シンニング
X thinning
(Dc ≥ 1.19mm)



【オリジナル商品】

●材質：超超微粒子超硬合金 ●表面処理：スムースコートコート ●外径許容差：0～-0.008mm

・ステンレス鋼などの小径加工に変革をもたらす



TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
OS31845	2.38	22	58	3	□
OS31846	2.39	22	58	3	□
OS31847	2.4	22	58	3	□
OS31848	2.41	22	58	3	□
OS31849	2.42	22	58	3	□
OS31850	2.43	22	58	3	□
OS31851	2.44	22	58	3	□
OS31852	2.45	22	58	3	□
OS31853	2.46	22	58	3	□
OS31854	2.47	22	58	3	□
OS31855	2.48	22	58	3	□
OS31856	2.49	22	58	3	□
OS31857	2.5	22	58	3	□
OS31858	2.51	22	58	3	□
OS31859	2.52	22	58	3	□
OS31860	2.53	22	58	3	□
OS31861	2.54	22	58	3	□
OS31862	2.55	22	58	3	□
OS31863	2.56	22	58	3	□
OS31864	2.57	22	58	3	□
OS31865	2.58	22	58	3	□
OS31866	2.59	22	58	3	□
OS31867	2.6	22	58	3	□
OS31868	2.61	22	58	3	□
OS31869	2.62	22	58	3	□
OS31870	2.63	22	58	3	□
OS31871	2.64	22	58	3	□
OS31872	2.65	22	58	3	□
OS31873	2.66	25	62	3	□
OS31874	2.67	25	62	3	□
OS31875	2.68	25	62	3	□
OS31876	2.69	25	62	3	□
OS31877	2.7	25	62	3	□
OS31878	2.71	25	62	3	□
OS31879	2.72	25	62	3	□
OS31880	2.73	25	62	3	□
OS31881	2.74	25	62	3	□
OS31882	2.75	25	62	3	□
OS31883	2.76	25	62	3	□
OS31884	2.77	25	62	3	□
OS31885	2.78	25	62	3	□
OS31886	2.79	25	62	3	□
OS31887	2.8	25	62	3	□
OS31888	2.81	25	62	3	□
OS31889	2.82	25	62	3	□
OS31890	2.83	25	62	3	□
OS31891	2.84	25	62	3	□
OS31892	2.85	25	62	3	□
OS31893	2.86	25	62	3	□
OS31894	2.87	25	62	3	□
OS31895	2.88	25	62	3	□
OS31896	2.89	25	62	3	□
OS31897	2.9	25	62	3	□
OS31898	2.91	25	62	3	□
OS31899	2.92	25	62	3	□
OS31900	2.93	25	62	3	□
OS31901	2.94	25	62	3	□

TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
OS31902	2.95	25	62	3	□
OS31903	2.96	25	62	3	□
OS31904	2.97	25	62	3	□
OS31905	2.98	25	62	3	□
OS31906	2.99	25	62	3	□
OS31907	3	25	62	3	□

●標準品 □オリジナル品

MRS-GDL


マイクロレボリューションドリル



フォーファセットポイント
Four Facet point
(Dc ≤ 1.19mm)



X形シンニング
X thinning
(Dc ≥ 1.19mm)



●材質：超超微粒子超硬合金 ●表面処理：スームコートコート ●外径許容差：0～-0.008mm

・ステンレス鋼などの小径加工に変革をもたらす



EDP.	TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
	OS31908	0.1	1.2	38	3	□
	OS31909	0.11	1.2	38	3	□
	OS31910	0.12	1.4	38	3	□
	OS31911	0.13	1.4	38	3	□
	OS31912	0.14	1.4	38	3	□
	OS31913	0.15	1.8	38	3	□
	OS31914	0.16	1.8	38	3	□
	OS31915	0.17	1.8	38	3	□
	OS31916	0.18	2.1	38	3	□
	OS31917	0.19	2.1	38	3	□
	OS31918	0.2	2.4	38	3	□
	OS31919	0.21	2.4	38	3	□
	OS31920	0.22	2.6	38	3	□
	OS31921	0.23	2.6	38	3	□
	OS31922	0.24	2.6	38	3	□
	OS31923	0.25	3	38	3	□
	OS31924	0.26	3	38	3	□
	OS31925	0.27	3	38	3	□
	OS31926	0.28	3.3	38	3	□
	OS31927	0.29	3.3	38	3	□
	OS31928	0.3	5	38	3	□
	OS31929	0.31	5	38	3	□
	OS31930	0.32	5	38	3	□
	OS31931	0.33	5	38	3	□
	OS31932	0.34	5	38	3	□
	OS31933	0.35	5	38	3	□
	OS31934	0.36	5	38	3	□
	OS31935	0.37	5	38	3	□
	OS31936	0.38	5	38	3	□
	OS31937	0.39	5	38	3	□
	OS31938	0.4	6	38	3	□
	OS31939	0.41	6	38	3	□
	OS31940	0.42	6	38	3	□
	OS31941	0.43	6	38	3	□
	OS31942	0.44	6	38	3	□
	OS31943	0.45	6	38	3	□
	OS31944	0.46	6	38	3	□
	OS31945	0.47	6	38	3	□
	OS31946	0.48	6	38	3	□
	OS31947	0.49	6	38	3	□
8577050	OS26816	0.5	6	42	3	A
	OS30341	0.51	6	42	3	□
	OS30342	0.52	6	42	3	□
	OS30343	0.53	6	42	3	□
8577054	OS26817	0.54	6.6	42	3	A
8577055	OS26818	0.55	6.6	42	3	A
8577056	OS26819	0.56	7.2	42	3	A
	OS30344	0.57	7.2	42	3	□
	OS30345	0.58	7.2	42	3	□
	OS30346	0.59	7.2	42	3	□
8577060	OS26820	0.6	7.2	42	3	A
	OS30347	0.61	7.8	46	3	□
	OS30348	0.62	7.8	46	3	□
8577063	OS26821	0.63	7.8	46	3	A
8577064	OS26822	0.64	7.8	46	3	A
8577065	OS26823	0.65	7.8	46	3	A
	OS30349	0.66	7.8	46	3	□

EDP.	TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
	OS30350	0.67	7.8	46	3	□
	OS30351	0.68	8.4	46	3	□
	OS30352	0.69	8.4	46	3	□
8577070	OS26824	0.7	8.4	46	3	A
8577071	OS26825	0.71	9	46	3	A
8577072	OS26826	0.72	9	46	3	A
8577073	OS26827	0.73	9	46	3	A
8577074	OS26828	0.74	9	46	3	A
8577075	OS26829	0.75	9	46	3	A
	OS30353	0.76	9.6	46	3	□
	OS30354	0.77	9.6	46	3	□
	OS30355	0.78	9.6	46	3	□
	OS30356	0.79	9.6	46	3	□
8577080	OS26830	0.8	9.6	46	3	A
8577081	OS26831	0.81	10.2	46	3	A
8577082	OS26832	0.82	10.2	46	3	A
	OS30357	0.83	10.2	46	3	□
	OS30358	0.84	10.2	46	3	□
	OS30359	0.85	10.2	46	3	□
	OS30360	0.86	10.8	46	3	□
	OS30361	0.87	10.8	46	3	□
	OS30362	0.88	10.8	46	3	□
	OS30363	0.89	10.8	46	3	□
8577090	OS26833	0.9	10.8	46	3	A
8577091	OS26834	0.91	11.4	46	3	A
8577092	OS26835	0.92	11.4	46	3	A
	OS30364	0.93	11.4	46	3	□
	OS30365	0.94	11.4	46	3	□
	OS30366	0.95	11.4	46	3	□
	OS30367	0.96	12	46	3	□
	OS30368	0.97	12	46	3	□
	OS30369	0.98	12	46	3	□
	OS30370	0.99	12	46	3	□
8577100	OS26836	1	12	46	3	A
	OS30371	1.01	12.6	50	3	□
	OS30372	1.02	12.6	50	3	□
	OS30373	1.03	12.6	50	3	□
	OS30374	1.04	12.6	50	3	□
	OS30375	1.05	12.6	50	3	□
	OS30376	1.06	12.6	50	3	□
	OS30377	1.07	13.2	50	3	□
	OS30378	1.08	13.2	50	3	□
	OS30379	1.09	13.2	50	3	□
8577110	OS26837	1.1	13.2	50	3	A
8577111	OS26838	1.11	13.8	50	3	A
8577112	OS26839	1.12	13.8	50	3	A
	OS30380	1.13	13.8	50	3	□
	OS30381	1.14	13.8	50	3	□
8577115	OS26840	1.15	13.8	50	3	A
	OS30382	1.16	13.8	50	3	□
	OS30383	1.17	13.8	50	3	□
	OS30384	1.18	13.8	50	3	□
	OS30385	1.19	14.4	50	3	□
8577120	OS26841	1.2	14.4	50	3	A
	OS30386	1.21	15	50	3	□
	OS30387	1.22	15	50	3	□
	OS30388	1.23	15	50	3	□

●標準品 □オリジナル品



MRS-GDL


マイクロレボリューションドリル



フォーフェイスポイント
Four-Facet point
(Dc ≦ 1.19mm)



X 形シンニング
X thinning
(Dc ≧ 1.19mm)



●材質：超超微粒子超硬合金 ●表面処理：スームコートコート ●外径許容差：0 - 0.008mm

・ステンレス鋼などの小径加工に変革をもたらす



EDP.	TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
	OS30389	1.24	15	50	3	□
	OS30390	1.25	15	50	3	□
	OS30391	1.26	15.6	50	3	□
8577127	OS26842	1.27	15.6	50	3	A
8577128	OS26843	1.28	15.6	50	3	A
8577129	OS26844	1.29	15.6	50	3	A
8577130	OS26845	1.3	15.6	50	3	A
	OS30392	1.31	16.2	54	3	□
	OS30393	1.32	16.2	54	3	□
	OS30394	1.33	16.2	54	3	□
	OS30395	1.34	16.2	54	3	□
	OS30396	1.35	16.2	54	3	□
	OS30397	1.36	16.8	54	3	□
	OS30398	1.37	16.8	54	3	□
	OS30399	1.38	16.8	54	3	□
	OS30400	1.39	16.8	54	3	□
8577140	OS26846	1.4	16.8	54	3	A
	OS30401	1.41	17.4	54	3	□
	OS30402	1.42	17.4	54	3	□
	OS30403	1.43	17.4	54	3	□
	OS30404	1.44	17.4	54	3	□
8577145	OS26847	1.45	17.4	54	3	A
8577146	OS26848	1.46	18	54	3	A
8577147	OS26849	1.47	18	54	3	A
	OS30405	1.48	18	54	3	□
	OS30406	1.49	18	54	3	□
8577150	OS26850	1.5	18	54	3	A
8577151	OS26851	1.51	18.6	54	3	A
8577152	OS26852	1.52	18.6	54	3	A
8577153	OS26853	1.53	18.6	54	3	A
	OS30407	1.54	18.6	54	3	□
8577155	OS26854	1.55	18.6	54	3	A
8577156	OS26855	1.56	19.2	54	3	A
8577157	OS26856	1.57	19.2	54	3	A
	OS30408	1.58	19.2	54	3	□
	OS30409	1.59	19.2	54	3	□
8577160	OS26857	1.6	19.2	54	3	A
	OS30410	1.61	19.8	58	3	□
	OS30411	1.62	19.8	58	3	□
	OS30412	1.63	19.8	58	3	□
	OS30413	1.64	19.8	58	3	□
	OS30414	1.65	19.8	58	3	□
	OS30415	1.66	20.4	58	3	□
	OS30416	1.67	20.4	58	3	□
	OS30417	1.68	20.4	58	3	□
	OS30418	1.69	20.4	58	3	□
8577170	OS26858	1.7	20.4	58	3	A
	OS30419	1.71	21	58	3	□
	OS30420	1.72	21	58	3	□
	OS30421	1.73	21	58	3	□
	OS30422	1.74	21	58	3	□
	OS30423	1.75	21	58	3	□
	OS30424	1.76	21.6	58	3	□
	OS30425	1.77	21.6	58	3	□
	OS30426	1.78	21.6	58	3	□
	OS30427	1.79	21.6	58	3	□
8577180	OS26859	1.8	21.6	58	3	A

EDP.	TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
8577181	OS26860	1.81	22.2	58	3	A
8577182	OS26861	1.82	22.2	58	3	A
8577183	OS26862	1.83	22.2	58	3	A
	OS30428	1.84	22.2	58	3	□
	OS30429	1.85	22.2	58	3	□
	OS30430	1.86	22.8	58	3	□
	OS30431	1.87	22.8	58	3	□
	OS30432	1.88	22.8	58	3	□
	OS30433	1.89	22.8	58	3	□
8577190	OS26863	1.9	22.8	58	3	A
	OS30434	1.91	23.4	58	3	□
	OS30435	1.92	23.4	58	3	□
	OS30436	1.93	23.4	58	3	□
	OS30437	1.94	23.4	58	3	□
	OS30438	1.95	24	58	3	□
	OS30439	1.96	24	58	3	□
	OS30440	1.97	24	58	3	□
8577198	OS26864	1.98	24	58	3	A
8577199	OS26865	1.99	24	58	3	A
8577200	OS26866	2	24	58	3	A
	OS30441	2.01	24.6	62	3	□
	OS30442	2.02	24.6	62	3	□
	OS30443	2.03	24.6	62	3	□
	OS30444	2.04	24.6	62	3	□
	OS30445	2.05	24.6	62	3	□
	OS30446	2.06	25.2	62	3	□
	OS30447	2.07	25.2	62	3	□
	OS30448	2.08	25.2	62	3	□
	OS30449	2.09	25.2	62	3	□
8577210	OS26867	2.1	25.2	62	3	A
	OS30450	2.11	25.8	62	3	□
8577212	OS26868	2.12	25.8	62	3	A
8577213	OS26869	2.13	25.8	62	3	A
8577214	OS26870	2.14	25.8	62	3	A
	OS30451	2.15	25.8	62	3	□
	OS30452	2.16	26.4	62	3	□
	OS30453	2.17	26.4	62	3	□
	OS30454	2.18	26.4	62	3	□
	OS30455	2.19	26.4	62	3	□
8577220	OS26871	2.2	26.4	62	3	A
	OS30456	2.21	27	62	3	□
	OS30457	2.22	27	62	3	□
	OS30458	2.23	27	62	3	□
	OS30459	2.24	27	62	3	□
	OS30460	2.25	27	62	3	□
	OS30461	2.26	27.6	62	3	□
	OS30462	2.27	27.6	62	3	□
	OS30463	2.28	27.6	62	3	□
8577229	OS26872	2.29	27.6	62	3	A
8577230	OS26873	2.3	27.6	62	3	A
8577231	OS26874	2.31	28.2	62	3	A
	OS30464	2.32	28.2	62	3	□
	OS30465	2.33	28.2	62	3	□
	OS30466	2.34	28.2	62	3	□
	OS30467	2.35	28.2	62	3	□
	OS30468	2.36	28.2	62	3	□
	OS30469	2.37	28.2	62	3	□

MRS-GDL


マイクロレボリューションドリル



フォーフェイスポイント
Four Facet point
(Dc ≤ 1.19mm)



X 形シンニング
X thinning
(Dc ≥ 1.19mm)



●材質：超超微粒子超硬合金 ●表面処理：スームコートコート ●外径許容差：0 - - 0.008mm

・ステンレス鋼などの小径加工に変革をもたらす



EDP.	TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
	OS30470	2.38	28.2	62	3	□
8577239	OS26875	2.39	28.8	62	3	A
8577240	OS26876	2.4	28.8	62	3	A
8577241	OS26877	2.41	29.4	66	3	A
8577242	OS26878	2.42	29.4	66	3	A
	OS30471	2.43	29.4	66	3	□
	OS30472	2.44	29.4	66	3	□
	OS30473	2.45	29.4	66	3	□
	OS30474	2.46	30	66	3	□
	OS30475	2.47	30	66	3	□
	OS30476	2.48	30	66	3	□
	OS30477	2.49	30	66	3	□
8577250	OS26879	2.5	30	66	3	A
	OS30478	2.51	30.6	66	3	□
	OS30479	2.52	30.6	66	3	□
	OS30480	2.53	30.6	66	3	□
	OS30481	2.54	30.6	66	3	□
8577255	OS26880	2.55	30.6	66	3	A
8577256	OS26881	2.56	31.2	66	3	A
8577257	OS26882	2.57	31.2	66	3	A
	OS30482	2.58	31.2	66	3	□
	OS30483	2.59	31.2	66	3	□
8577260	OS26883	2.6	31.2	66	3	A
	OS30484	2.61	31.8	66	3	□
	OS30485	2.62	31.8	66	3	□
	OS30486	2.63	31.8	66	3	□
	OS30487	2.64	31.8	66	3	□
	OS30488	2.65	31.8	66	3	□
	OS30489	2.66	32.4	66	3	□
	OS30490	2.67	32.4	66	3	□
	OS30491	2.68	32.4	66	3	□
	OS30492	2.69	32.4	66	3	□
8577270	OS26884	2.7	32.4	66	3	A
	OS30493	2.71	33	66	3	□
	OS30494	2.72	33	66	3	□
	OS30495	2.73	33	66	3	□
	OS30496	2.74	33	66	3	□
	OS30497	2.75	33	66	3	□
	OS30498	2.76	34.2	66	3	□
8577277	OS26885	2.77	33.6	66	3	A
8577278	OS26886	2.78	33.6	66	3	A
8577279	OS26887	2.79	33.6	66	3	A
8577280	OS26888	2.8	33.6	66	3	A
	OS30499	2.81	34.2	66	3	□
	OS30500	2.82	34.2	66	3	□
	OS30501	2.83	34.2	66	3	□
	OS30502	2.84	34.2	66	3	□
	OS30503	2.85	34.2	66	3	□
	OS30504	2.86	34.8	66	3	□
	OS30505	2.87	34.8	66	3	□
	OS30506	2.88	34.8	66	3	□
	OS30507	2.89	34.8	66	3	□
8577290	OS26889	2.9	34.8	66	3	A
	OS30508	2.91	35.4	66	3	□
	OS30509	2.92	35.4	66	3	□
	OS30510	2.93	35.4	66	3	□
	OS30511	2.94	35.4	66	3	□

EDP.	TY コード	刃径 (Dc)	溝長 (ℓ)	全長 (L)	シャンク (Ds)	分類
	OS30512	2.95	35.4	66	3	□
	OS30513	2.96	36	66	3	□
	OS30514	2.97	36	66	3	□
	OS30515	2.98	36	66	3	□
	OS30516	2.99	36	66	3	□
8577300	OS26890	3	36	66	3	A